

34208A

SPECIFICATIONS

±250 g, ±500 g Triaxial Accelerometer Wide Bandwidth to 10 kHz Precision Aligned

This Measurement Specialties product is subject to U.S. Export Law

Precisely Measure Real -World Accelerations

The Measurement Specialties 34208A accelerometer has each mutually orthogonal axis precisely aligned within 0.75 degree of the theoretical ideal. This provides the accuracy required by most measurement applications without any compensation. Critical applications requiring higher accuracy can use the alignment data provided on the calibration certificate to compensate for any small residual error.

Choose the bandwidth and range options best suited for your application to measure up to ±250 g or ±500 g accelerations on each of three axes.

Each axial sensor has been tested over the -40 to +85°C temperature range and has a nominal full scale output swing of ±2 volts. The zero g output level is nominally +2.5 volts. Precise values for each axis are available on the included calibration certificate.

FEATURES

Precision Alignment

Each axis of the Measurement Specialties 34208A is precision aligned to minimize errors due to axis misalignment or transverse sensitivity.

High Accuracy and Linearity over Wide Temperature Range

The voltage output for each axis of the 34208A is directly proportional to the acceleration along that axis. Each DC-coupled output is fully scaled, referenced, and temperature compensated over the entire -40 to +85°C range. Accuracy is improved by minimizing variations due to temperature and aging effects, resulting in a sensor that is more stable over temperature than piezoelectric or piezoresistive devices.

Calibration Certificate

Each 34208A is supplied with a calibration certificate listing sensitivity and offset, as well as on-axis and transverse alignment parameters needed to ensure rapid and efficient system implementation. The alignment data can be used to compensate the measured values to achieve an even higher level of sensor accuracy.



Self-Test on Digital Command

A TTL-compatible self-test low input causes a simulated acceleration to be injected into all three sensors to verify channel integrity.

Small Size

Complete conditioned triaxial accelerometer in less than a cubic inch.

-Built-In Power Supply Regulation

Unregulated DC power from +8.5 to +36 volts is all that is required to measure acceleration and temperature.

Suitable for Harsh Environments

The 34208A is robust and can be used in harsh environments. The unit will survive 4000 g powered or unpowered.

Warranty


These Measurement Specialties accelerometers come with a three-year factory warranty.

SPECIFICATIONS FOR 34208A - *improved specifications available upon request*


T_a = T_{min} to T_{max}; 8.5 ≤ V_s ≤ 36 V; Acceleration = 0 g unless otherwise noted; within one year of calibration.

Parameter	Min	Typical	Max	Units	Conditions/Notes
Accelerometers Full Scale Range					On each axis, specify with Option Rnnn
Option R250		±250		g	
Option R500		±500		g	
Sensitivity at 25°C					
Option R250		±8		mV/g	
Option R500		±4		mV/g	
Drift T _{min} to T _{max}		1% (TBD)		%	Percent of sensitivity at 25°C
Zero g Bias Level					
At 25°C		2.5 ±0.010		V	Precise values on cal certificate
Drift T _{min} to T _{max} At 1.25°C/min rate of change		±1000		mg	
Alignment					Precise values on cal certificate
Deviation from Ideal Axes			±0.75	degree	Can be compensated if required
Transverse Sensitivity		±0.25		%	Inherent sensor error, excluding misalignment
Nonlinearity		0.2	2	% FSR	Best fit straight line
Frequency Response	0		10	kHz	Upper cutoff per Option Bnnn, -3 dB pt ±10%
Noise Density		±2.8		mg/√Hz	10 Hz to 400 Hz
Self-Test Input Impedance	10			kΩ	Pullup. Logic "1" ≥3.5V, Logic "0" ≤1.5V
Temperature Sensor					Accuracy ±1°C
Sensitivity		6.45		mV/°C	
0°C Bias Level		509		mV	
Outputs					
Output Voltage Swing	0.50		4.50	V	I _{out} = ±0.5 mA
Capacitive Drive Capability	1000			pF	
Power Supply (V_s)					
Input Voltage Limits	-20		+38	V	-20V continuous
Input Voltage - Operating	+8.5		+36	V	
Input Current		15	20	mA	No load, quiescent
Rejection Ratio		>120		dB	DC
Temperature Range (T_a)	-40		+85	°C	
Mass		35		grams	Precise values on cal certificate
Shock Survival	-4000		+4000	g	Any axis for 0.5ms, powered or unpowered

MECHANICAL




CONNECTIONS



Pin	1	2	3	4	5	6	7	8	9
Signal	A1+	Signal-	A2+	+5VOut	A3+	T+	Self Test-L	+Vs	Gnd
Wire	Brown	Red	Orange	Yellow	Green	Blue	Violet	Grey	White

ORDERING INFORMATION



NORTH AMERICA

Measurement Specialties, Inc.,
 a TE Connectivity Company
 2236 N. Cleveland-Massillon Road
 Akron, OH 44333
 USA
 Tel: +1-330-659-3312
 Sales: pvg.cs.amer@meas-spec.com

EUROPE

MEAS France SAS
 a TE Connectivity Company
 26 Rue des Dames
 F78340 Les Clayes-sous-Bois
 France
 Tel: +33 (0) 130 79 33 00
 Fax: +33(0) 134 81 03 59
 Sales: pfg.cs.emea@meas-spec.com

ASIA

Measurement Specialties (China), Ltd.,
 a TE Connectivity Company
 No. 26 Langshan Road
 Shenzhen High-Tech Park (North)
 Nanshan District, Shenzhen 518057
 China
 Tel: +86 755 3330 5088
 Fax: +86 755 3330 5099
 Sales: pfg.cs.asia@meas-spec.com

TE.com/sensorsolutions

Measurement Specialties, Inc., a TE Connectivity company.

Measurement Specialties, TE Connectivity, TE Connectivity (logo) and EVERY CONNECTION COUNTS are trademarks. All other logos, products and/or company names referred to herein might be trademarks of their respective owners.

The information given herein, including drawings, illustrations and schematics which are intended for illustration purposes only, is believed to be reliable. However, TE Connectivity makes no warranties as to its accuracy or completeness and disclaims any liability in connection with its use. TE Connectivity's obligations shall only be as set forth in TE Connectivity's Standard Terms and Conditions of Sale for this product and in no case will TE Connectivity be liable for any incidental, indirect or consequential damages arising out of the sale, resale, use or misuse of the product. Users of TE Connectivity products should make their own evaluation to determine the suitability of each such product for the specific application.

© 2015 TE Connectivity Ltd. family of companies All Rights Reserved.