



# MODEL 64C ACCELEROMETER



## DIMENSIONS



## SPECIFICATIONS

- DC Response Accelerometer
- Durable Low Noise Cable
- Small Package
- SAE J2570 Compliant

The Model 64C Accelerometer is based on an advanced piezoresistive MEMS sensing element which offers exceptional dynamic range and stability. This unit features a full bridge output configuration with a compensated temperature range from 0 to +50° C. A slight amount of internal gas damping provides outstanding shock survivability and a flat amplitude and phase response up to 7kHz. The Model 64C is compliant with SAE J211 standards for anthropomorphic dummy instrumentation.

## FEATURES

- Piezoresistive MEMS Sensor
- ±50g to ±6,000g Ranges
- 2-10 Vdc Excitation
- -40 to +121°C Temp Range
- Low Noise Jacketed Cable
- 1% Transverse Sensitivity Option
- <±25 mV Zero Offset

## APPLICATIONS

- Safety Crash Testing
  - Auto
  - Truck
  - Recreational Vehicles
- Shock Testing

**PERFORMANCE SPECIFICATIONS**

All values are typical at  $\pm 24^{\circ}\text{C}$ , 80Hz and 10Vdc excitation unless otherwise stated. Measurement Specialties reserves the right to update and change these specifications without notice.

**Parameters**

**DYNAMIC**

	$\pm 50$	$\pm 100$	$\pm 200$	$\pm 500$	$\pm 2000$	$\pm 6000$	<b>Notes</b>
Range(g)	$\pm 50$	$\pm 100$	$\pm 200$	$\pm 500$	$\pm 2000$	$\pm 6000$	
Sensitivity (mV/g) <sup>1</sup>	2	0.9	0.8	0.4	0.15	0.10	
Frequency Response (Hz)	0-400	0-500	0-600	0-800	0-3000	0-3000	$\pm 2\%$
	0-1000	0-1200	0-1400	0-2000	0-5000	0-5000	$\pm 1/2\text{dB}$
	0-1400	0-1500	0-1900	0-2800	0-7000	0-7000	$\pm 1\text{dB}$
Resonant Frequency (Hz)	4000	6000	8000	15000	26000	26000	
Damping Ratio	0.5	0.5	0.5	0.3	0.05	0.05	Typical
Shock Limit (g)	5000	5000	5000	10000	10000	10000	
Non-Linearity (% of reading)	$\pm 1$	$\pm 1$	$\pm 1$	$\pm 1$	$\pm 1$	$\pm 1$	
Transverse Sensitivity (%)	<3	<3	<3	<3	<3	<3	<1% Option

**ELECTRICAL**

Zero Acceleration Output (mV)	$<\pm 25$						$<\pm 10\text{mV}$ Option
Excitation (Vdc)	2 to 10						
Input Resistance ( $\Omega$ )	2400-6000						
Output Resistance ( $\Omega$ )	2400-6000						
Insulation Resistance (M $\Omega$ )	>100						@100Vdc
Residual Noise ( $\mu\text{V RMS}$ )	<10						
Ground Isolation	Isolated from mounting surface						

**ENVIRONMENTAL**

Thermal Zero Shift (%FSO/ $^{\circ}\text{C}$ )	$\pm 0.04$						From 0 to $+50^{\circ}\text{C}$
Thermal Sensitivity Shift (%/ $^{\circ}\text{C}$ )	$-0.20 \pm 0.05$						From 0 to $+50^{\circ}\text{C}$
Operating Temperature ( $^{\circ}\text{C}$ )	-40 to +121						
Storage Temperature ( $^{\circ}\text{C}$ )	-40 to +121						
Humidity	Epoxy Sealed, IP61						

**PHYSICAL**

Case & Cover Material	Anodized Aluminum						
Cable (Integral 30 Foot Cable)	4x #32 AWG Conductors PFA Insulated, Braided Shield, TPE Jacket						
Weight (grams)	1.0						Cable Not Included
Mounting	2x #0-80 x 3/16" Socket Head Cap Screws						Torque 3 lb-in

<sup>1</sup> Output is ratiometric to excitation voltage

**Calibration supplied:** CS-FREQ-0100 NIST Traceable Amplitude Calibration from 20Hz to  $\pm 1\text{dB}$  Frequency Limit


**Supplied accessories:** AC-A02053 2x #0-80 (3/16 length) Socket Head Cap Screw, 2x #0 Washer, 1x Allen Key

**Optional accessories:** MTG-E2 Triaxial Mounting Block  
 121 3-Channel Precision Low Noise DC Amplifier  
 140A Auto-Zero Inline Amplifier

The information in this sheet has been carefully reviewed and is believed to be accurate; however, no responsibility is assumed for inaccuracies. Furthermore, this information does not convey to the purchaser of such devices any license under the patent rights to the manufacturer. Measurement Specialties, Inc. reserves the right to make changes without further notice to any product herein. Measurement Specialties, Inc. makes no warranty, representation or guarantee regarding the suitability of its product for any particular purpose, nor does Measurement Specialties, Inc. assume any liability arising out of the application or use of any product or circuit and specifically disclaims any and all liability, including without limitation consequential or incidental damages. Typical parameters can and do vary in different applications. All operating parameters must be validated for each customer application by customer's technical experts. Measurement Specialties, Inc. does not convey any license under its patent rights nor the rights of others.

Notes: ---SAE J2570 Corridor

**Typical Frequency Response**



**ORDERING INFORMATION**

**PART NUMBERING** Model Number+Range+Cable Length+Options

64C-GGGG-CCCT-ZZZ

|     |     |     |     Options  
 |     |     |     |     1% Transverse Sensitivity when "T" is present.  
 |     |     |     |     Cable (360 is 360 inches)  
 |     |     |     |     Range (0100 is 100g)

**Optional Dash Numbers**  
 -001   5Vdc Calibration  
 -004   ZMO <10mV  
 -005   2Vdc Calibration

Example: 64C-2000-360T  
 Model 64C, 2000g, 360" (30ft) Cable), 1% Transverse Sensitivity

**NORTH AMERICA**

Measurement Specialties, Inc.,  
 a TE Connectivity Company  
 1000 Lucas Way  
 Hampton, VA 23666  
 Sales and Customer Service  
 Tel: +1-800-745-8008 or  
 +1-757-766-1500  
 Fax: +1-757-766-4297  
 t&m@meas-spec.com

**EUROPE**

MEAS France SAS  
 a TE Connectivity Company  
 26 Rue des Dames  
 F78340 Les Clayes-sous-Bois  
 France  
 Sales and Customer Service  
 Tel: +33 (0) 1 79 33 00  
 Fax: +33(0)1 34 81 03 59  
 t&m@meas-spec.com

**ASIA**

Measurement Specialties (China), Ltd.,  
 a TE Connectivity Company  
 No. 26 Langshan Road  
 Shenzhen High-Tech Park (North)  
 Nanshan District, Shenzhen 518057  
 China  
 Sales and Customer Service  
 Tel: +86 755 3330 5088  
 Fax: +86 755 3330 5099  
 t&m@meas-spec.com

**TE.com/sensorsolutions**

Measurement Specialties, Inc., a TE Connectivity company.

Measurement Specialties, TE Connectivity, TE Connectivity (logo) and EVERY CONNECTION COUNTS are trademarks. All other logos, products and/or company names referred to herein might be trademarks of their respective owners.

The information given herein, including drawings, illustrations and schematics which are intended for illustration purposes only, is believed to be reliable. However, TE Connectivity makes no warranties as to its accuracy or completeness and disclaims any liability in connection with its use. TE Connectivity's obligations shall only be as set forth in TE Connectivity's Standard Terms and Conditions of Sale for this product and in no case will TE Connectivity be liable for any incidental, indirect or consequential damages arising out of the sale, resale, use or misuse of the product. Users of TE Connectivity products should make their own evaluation to determine the suitability of each such product for the specific application.

© 2015 TE Connectivity Ltd. family of companies All Rights Reserved.

**DEALER / REVENDEDOR**

Brazil and South America / Brasil e América do Sul



**Address / Endereço:**

Rua Sete de Setembro, 2656  
13560-181 - São Carlos - SP  
Brazil / Brasil

**Phone / Telefone:**

+55 (16) 3371-0112  
+55 (16) 3372-7800

**Internet:**

[www.metrolog.net](http://www.metrolog.net)  
[metrolog@metrolog.net](mailto:metrolog@metrolog.net)

**[www.metrolog.net](http://www.metrolog.net)**