OPTICAL LINEAR ENCODER

"Thick Body, Long Distance Measurement"

ALS-6

- Optical measurement
- Measuring lengths from 50 mm to 3200 mm
- High resolution up to 1 µm
- ±10 µm accuracy
- 5 ball bearing system
- Single seal protection
- 5 VDC TTL quadrature or 1vpp sinusoidal output signal
- Easy mounting
- 60 m/min traveling speed

ALS series optical linear encoder systems are protected from factors such as dust, shavings, dirt and coolant with its compact design. ALS6 series, which has optical measuring principle with glass ruler, can measure between 50 and 3200 mm.

APPLICATIONS

- Manuel Benches
- Press Brakes and Bending Machines
- Robotic / Material Packaging

Linear Bearing Systems
Automation and Robotic Applications
Textile Machinery

Transfer Machines
Turning, Milling
Woodworking machines etc.

TECHNICAL FEATURES

Measuring Type	Optical
Measuring Lengths	Different lengths from 50 mm to 3200 mm
Resolution	1µm, 5µm or 1Vpp sinusoidal
Signal Period	20 µm
Accuracy	± 10 µm
Repeatability	± 1 pulse
Max traveling speed	60m/min
Supply Voltage	5 VDC
Output Type	5V TTL or 1Vpp Sinusoidal

Reference Mark	1 reference mark at every 50 mm
Body Material	Aluminum
Operating Temperature	0°C…50 °C
Storage Temperature	-20°C…70 °C
Protection Class	IP54
Electrical Connection	Spiral cable and socket (For TTL Signal:D-SUB 9 pin male socket / For Sinus Signal: M16/8 pin female socket)
Max cable length	50-500mm (3m armoured cable) 600-2000mm (5m armoured cable)

ELECTRICAL CONNECTIONS

PIN NO	CABLE COLOR	D-SUB 9 PIN SOCKET TTL SIGNAL	M16/8 PIN FEMALE SOCKET SINUS SIGNAL
1	WHITE	A	0°
2	BROWN	/B	180°
3	RED	+5VDC	+5VDC
4	BLACK	0V-GND	0V-GND
5	BLUE	/A	90°
6	GREEN	B	270°
7	YELLOW	/Z	Z
8	GREY	Z	N/C

In the table, the cable colors of sensors output signals are given. If the control circuit is suitable, in the line driver sensors, the not signals (/A, /B, /Z) have to be added to the system. If it is not suitable /A, /B, /Z signal cables must be fixed as insulated separately. Don't forget that these edges have electricity too.

MECHANICAL DIMENSIONS



L₀: Measuring Length (mm) (Different lengths from 50 to 3200 mm
L₁: Distance between mounting holes (mm)
L : Body Length (mm)

ORDER CODE

Model		Resolution		Measuring Length
ALS 6	-	XX	-	XXX

Measuring Length
Different lengths from 50 mm to 3200 mm

Resolution
01 : 1µm
05 : 5µm
S : Sinusoidal

Atek Elektronik Sensör Teknolojileri Sanayi ve Ticaret A.Ş.

Gebze OSB, 800. Sokak, No:814 Gebze/KOCAELİ/TURKEY

Tel: +90 262 673 76 00 Fax: +90 262 673 76 08

www.ateksensor.com info@ateksensor.com

DISTRIBUTOR / DISTRIBUIDOR

Brazil and South America / Brasil e América do Sul

www.metrolog.net

Metrolog Controles de Medição

Address / Endereço:

Rua Sete de Setembro, 2656
13560-181 - São Carlos - SP
Brazil / Brasil

Phone / Telefone:

+55 (16) 3371-0112
+55 (16) 3372-7800

Internet:

www.metrolog.net
metrolog@metrolog.net