



*The LVDT/A & LVDT/D provide a wide range of signal conditioning for LVDT transducers.*



### User Benefits

- Sensor excitation
- Selectable sensitivity
- User selectable analogue outputs
- High frequency filtering

### Introduction

The LVDT has a wide range of output options for current, voltage (both uni-polar or bi-polar) which can be configured by setting the on-board DIL switches.

A wide frequency response is offered, of typically DC to 200Hz. There is an on-board low pass filter which can be switched in to reduce high frequency fluctuations or induced electrical noise, to give stable readings under adverse conditions.


Both the AC (115/230 V) and DC (18 -24 V) versions are based on a common board and are mounted in a light grey ABS enclosure sealed to IP65 standard.

### Specification at a Glance

- Sensor excitation of 4.5 V RMS
- Selectable excitation frequency between 1 & 5 KHz
- Selectable sensitivity from 20 mV to 10 V & fine trim with potentiometer
- Wide bandwidth (20 HZ) for test & measurement applications
- Selectable analogue output in voltage or current loop format including 4-20 mA and 10 VDC
- 3 year manufacturer's warranty
- Full CE approval
- IP65 / NEMA 4 enclosure dimensions 160 x 80 x 55 mm

### Ideal Applications

- Test & Measurement
- Alternative Energy
- Silo & Weighing
- Food Industry



## Related Product



### SMP

Universal display with analogue outputs, relays & data output



### UAB

Universal digital signal conditioner and controller

## CE & Environmental

Storage temperature	- 10 °C to +50°C
Operating temperature	- 20 °C to +70°C
Relative humidity	95% maximum non condensing
IP Rating	IP65 / NEMA 4

### CE Environmental Approvals

European EMC Directive	2004/108/EC
Low Voltage Directive	2006/95/EC

*For more information contact us today...*

mantracourt.com  
 technical@mantracourt.com  
 Mantracourt Electronics Ltd  
 The Drive, Farringdon, Exeter,  
 Devon, EX5 2JB, UK  
 tel: +44 (0) 1395 232020  
 fax: +44 (0) 1395 233190



In the interests of continued product development, Mantracourt Electronics Limited reserves the right to alter product specifications without prior notice

## Distribuidor

**Brasil e América do Sul**

### CONTATO

#### Endereço

Rua Sete de Setembro, 2656 - Centro  
13560-181 - São Carlos - SP - Brasil

#### Telefone

+ 55 (16) 3371-0112  
+ 55 (16) 3372-7800

#### Internet

[www.metrolog.net](http://www.metrolog.net)  
[metrolog@metrolog.net](mailto:metrolog@metrolog.net)

