

BASE STATION COMPARISON

FREE SOFTWARE:
Configure all our devices with our Toolkit. View and log data with LOG100. Just plug and play!



T24-BSd
Module size (H x W x L): 11 x 20.5 x 58 mm
Wireless Range: 500 m
Power supply: USB (4.875 to 5.125 Vdc)
Antenna: Integral (part of board)
Radio frequency: 2.4 GHz
Transmit power: 10 mW
Interface: USB
Operating temperature: -20 °C to +55 °C
Storage temperature: -40 °C to +85 °C
Environmental Protection: IP50
Software & Configurations: T24-Toolkit & T24-LOG100
USPs: <ul style="list-style-type: none"> - Very portable - Ideal for use with laptops & tablets - Smallest and most economically priced base station in our range



T24-BSu
Module size (H x W x L): 20 x 35 x 76 mm
Wireless Range: 500 m
Power supply: USB (4.875 to 5.125 Vdc)
Antenna: Integral (part of board)
Radio frequency: 2.4 GHz
Transmit power: 10 mW
Interface: USB
Operating temperature: -20 °C to +55 °C
Storage temperature: -40 °C to +85 °C
Environmental Protection: IP50
Software & Configurations: T24-Toolkit & T24-LOG100
USPs: <ul style="list-style-type: none"> - Wall mounted or desktop use - Can be moved independently of a laptop to achieve better reception



T24-BSue
Module size (H x W x L): 34 x 62 x 80 mm
Wireless Range: 800 m
Power supply: USB (4.875 to 5.125 Vdc)
Antenna: T24-ANTA (inside enclosure)
Radio frequency: 2.4 GHz
Transmit power: 10 mW
Interface: USB
Operating temperature: -20 °C to +55 °C
Storage temperature: -40 °C to +85 °C
Environmental Protection: IP67 / Nema4 (95% non-condensing max humidity level)
Software & Configurations: T24-Toolkit & T24-LOG100
USPs: <ul style="list-style-type: none"> - Wall mounted or desktop use. - Can be moved independently of a laptop to achieve better reception - Improved IP rating & greater range



T24-BSi
Module size (H x W x L): 57 x 84 x 164 mm
Wireless Range: 800 m
Power supply: USB or 9 to 32 Vdc (supply current at 12V: 100mA)
Antenna: T24-ANTA (inside enclosure)
Radio frequency: 2.4 GHz
Transmit power: 10 mW
Interface: USB / RS232 / RS485
Operating temperature: -20 °C to +55 °C
Storage temperature: -40 °C to +85 °C
Environmental Protection: IP67 / Nema4 (95% non-condensing max humidity level)
Software & Configurations: T24-Toolkit & T24-LOG100
USPs: <ul style="list-style-type: none"> - Wall mounted or desktop use - Can be moved independently of a laptop to achieve better reception - Data collection for PC/PLC; Has USB/RS232/RS485 interface

Distribuidor

Brasil e América do Sul

CONTATO

Endereço

Rua Sete de Setembro, 2656 - Centro
13560-181 - São Carlos - SP - Brasil

Telefone

+ 55 (16) 3371-0112
+ 55 (16) 3372-7800

Internet

www.metrolog.net
metrolog@metrolog.net

